



9700050
Revision
06/10/15

2RZ/3RZ/3VZ/2TR Billet Flex Fan Spacer Kit

Contents of Kit:

1 Billet Fan Spacer	4 M8-1.25 x 16mm Hex Bolts
8 M8 Flat Washers	4 M8-1.25 x 30mm Hex Bolts

Installation Instructions:

- Loosen bolts that hold the fan to the water pump.
 - Do not remove them just loosen them while the belt is still on to make removal easier.
- Remove water pump belt and then remove fan assembly from water pump.
 - You can also remove the fan shroud for extra room but this is not necessary.
- Remove stock fan studs in water pump and chase hub threads with a tap.
- Install the flex fan on the fan spacer using the shorter M8 Hex Bolts and M8 flat washers.
 - Use a mild thread locking compound on bolts.
- Install hub and fan assembly on the water pump flange using the longer M8 hex bolts and M8 flat washers.
- Rotate engine by hand, checking for fan clearance before starting engine.

2031 Holly Avenue, Lake Havasu City, AZ 86404
Office 928.505.2501 Fax 928.505.2503



9700050
Revision
06/10/15

2RZ/3RZ/3VZ/2TR Billet Flex Fan Spacer Kit

Contents of Kit:

1 Billet Fan Spacer	4 M8-1.25 x 16mm Hex Bolts
8 M8 Flat Washers	4 M8-1.25 x 30mm Hex Bolts

Installation Instructions:

- Loosen bolts that hold the fan to the water pump.
 - Do not remove them just loosen them while the belt is still on to make removal easier.
- Remove water pump belt and then remove fan assembly from water pump.
 - You can also remove the fan shroud for extra room but this is not necessary.
- Remove stock fan studs in water pump and chase hub threads with a tap.
- Install the flex fan on the fan spacer using the shorter M8 Hex Bolts and M8 flat washers.
 - Use a mild thread locking compound on bolts.
- Install hub and fan assembly on the water pump flange using the longer M8 hex bolts and M8 flat washers.
- Rotate engine by hand, checking for fan clearance before starting engine.

2031 Holly Avenue, Lake Havasu City, AZ 86404
Office 928.505.2501 Fax 928.505.2503